T1S R1W DUCHESNE COUNTY MONUMENT SURVEY RECORD 1/4 SURVEY MARKER AND WASHER SEC 30+SEC 29 AT 1/16 CORNER U.S.B.&M. 00.19,45 G-51311.90 29 ₹ MONUMENT SPIKE (HARROW TOOTH) `AT 1/4 CORNEŔ 00.07,41" NORTH NOTE: THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED FROM G.P.S. OBSERVATIONS AT A CONTROL POINT (SECTION CORNER) LOCATED AT LAT. 40"23"20.57790"N AND LONG. 110"01"46.98583"W USING THE UTAH STATE G.P.S. VIRTUAL REFERENCE STATION CONTROL NETWORK MAINTAINED AND OPERATED BY THE AUTOMATED GEOGRAPHIC REFERENCE CENTER SCALE: 1"=30' 0' *30'* BRASS CAP AT

SECTION CORNER

DESCRIPTION OF CORNER EVIDENCE FOUND

FOUND A MONUMENET SPIKE (HARROW TOOTH) AT THE POSITION OF THE 1/4 CORNER

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THE CORNER

SET SURVEY MARKER & BRASS WASHER AT POSITION OF 1/4 CORNER. USED ADJOINING CORNERS AS REFERENCE POINTS AS SHOWN

STATE PLANE COORDINATE DATA

(U.S. SURVEY FEET) NAD83 UTAH CENTRAL ZONE N: 7305910.648 E: 2050103.413 NAVD88 EL: 5519.79'

40°22'02.51474" N LATITUDE: LONGITUDE: 110°01'46.64537" W

ELLIPSOID HEIGHT: 5464.45'

(GEOID 03 CONUS)

PUBLIC LAND SURVEY SYSTEM GCDB ID NO.

UT300010S0010W0_200240

CERTIFICATION

Jerry D. Allred _ , Professional Land Surveyor, State of Utah, do hereby certify that I have performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve same

Date <u>28 FEB 2018</u>

Jerry D. Allred, Professional Land Surveyor Certificate No. 148951 Duchesne County Surveyor



